

Centrifuge

01 02 03 04 09 10

Technical specifications MANUAL centrifuge

| Model | Motor | Power | Max. Flow | Max. RPM | Dimensions mm | Weight kg |
|---------|-------------------------------|---------|-----------|----------|------------------|-----------|
| TRS30-M | 240 - 400 V x 3 50 - 60 Hz | 0,75 KW | 30 ltr/m | 3000 | 397 x 712 x 1010 | 155 kg |
| TRS50-M | | 1,5 KW | 50 ltr/m | 3000 | 470 x 787 x 1029 | 160 kg |
| TRS80-M | | 2,3 KW | 80 ltr/m | 3000 | 685 x 878 x 1444 | 240 kg |



Technical specifications AUTOMATIC centrifuge

| Model | Motor | Power | Max. Flow | Max. RPM | Dimensions mm | Weight kg |
|----------|-------------------------------|---------|-----------|----------|-------------------|-----------|
| TRS100-A | 240 - 400 V x 3 50 - 60 Hz | 3,70 KW | 100 ltr/m | 3.000 | 630 x 1100 x 1768 | 650 kg |
| TRS200-A | | 5,5 KW | 200 ltr/m | 2.500 | 730 x 1200 x 1768 | 750 kg |



Important notes:

- The flow rates mentioned are for water based fluids. In case of oil, the maximum flow rate will be 50% of the indicated flow.
- Standard models showing.
- Contact your local distributor for further information.